

ACE RailRunner

Remote Head	
Camera	Small Chip Block camera
Lens	Canon, Sony, Fujinon
Remote Head	Nettmann MicroPlus
Lens Height (From floor / support)	RailRunner with MicroPlus - 16" center of lens to floor.
Track Sizes	
Straight ENT Track	2m (6.6') Sections - Black
Width for safe clearance of track	10"
Width for safe clearance of camera and head	15"
Height for clearance	20"
Track Speeds	
Optimal Speeds	3.3 - 9.8 fps / 1-3 mps
Max Speed	15 fps / 5 mps
Max Acceleration	User controlled ramps
Dimensions (inches) & Weights (Lbs)	
Dolly - LxWxH	36"x8"x3.5" - 23 lbs
Track - LxWxH	78.74"x8"x2" - 25 lbs
Motor	12"x10"x10" - 25 lbs
Re-Direct unit	8"x2"x6" - 10 lbs
Track Control	
Operator Options	Joystick, pedals, computer, touchscreen
Special Requirements	
Track Power and Cabling	
Power Requirements	230V Single Phase (20AMP Circuit) Twist Lock Connectors If 230V is not available, Optional 120V to 230V Transformer needed.
Shipping Weights and Sizes	
Gross Weight - RailRunner	Depends on Track Needs
15 Cases @ Aprox	~ 1,200 lbs Total



WWW.ACEEAST.COM