

ACE TrackRunner Mini

Remote Head	
Camera	Panasonic AK-HC 1500G 2/3" Camera / Chip Block
Lens	Fujinon HD 7.6mm-136.8mm (Standard Suplied)) Accepts any Canon or Fujinon. Please NOTE: If using a 2 servo lens, an outboard Focus Servo must be provided. ACE can provide a FUJI focus servo. If using a Cannon lens, a tri-servo Lens or a Cannon Focus servo must be provided.
Remote Head	Nettmann MicroPlus, MiniMote
Lens Height (From floor / support)	MicroPlus Lens Height - ~17.5"
Track Sizes	
Straight ENT Track	2m (6.6') Sections - Black
Width of track	6 3/8"
Width of track feet	10 1/4"
Track Height	3 1/4"
Width for safe clearance of camera and head	20"
Track Speeds	
Max Speed - With Energy Chain (Cable Management)	20fps = ~15mph
Max Accesleration - With Energy Chain (Cable Management)	Fully adjustable speed ramps
Track Control	
Operator Options	Joystick, pedals, computer, touchscreen
Special Requirements	
Track Power and Cabling	
Power Requirements	230V Tech Power / 110v with use of ACE Transformers
Built in Cable Management	Pre-built or assembled to production needs (Fiber, Paint, etc)
Shipping Weights and Sizes	
	Sizes in inches / lbs
TrackRunner Mini - full system Shipping case	86"x34"x33" / 550 lbs



WWW.ACEEAST.COM